










**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

Harris Corporation expressly reserves the right to supplement or modify these Disclosures as appropriate upon receipt of further information and discovery. The Huawei '678 Patent Accused Products (as that term is defined and the corresponding devices are identified in Harris's P.R. 3-1 and P.R. 3-2 disclosures cover pleading) infringe at least the following claims. References to instrumentalities in this chart are exemplary only and should not be construed as limiting the scope of any claim of the '678 patent. The Huawei '678 Patent Accused Products satisfy each claim element below literally. The Huawei '678 Patent Accused Products also satisfy claim elements under the Doctrine of Equivalents, including without limitation where specifically identified below, because they include and perform substantially similar functionality.

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
A wireless local or metropolitan area network comprising:	<p>The Huawei '678 Patent Accused Products infringe this claim. Huawei makes, uses, sells, offers to sell and/or imports equipment used in wireless local or metropolitan area networks, including its WLAN products and consumer devices, and on information and belief, makes, uses, sells, offers to sell and/or imports wireless local or metropolitan area networks in the United States.</p> <p>Without the benefit of discovery, Harris identifies exemplary networks, including, without limitation, networks deployed at Huawei's 13 U.S. facilities; networks deployed in CloudCampus solutions such as those deployed for Cloud4Wi, in San Francisco, CA; other enterprise networks deployed for Weichai Power in Chicago, Ill., and Crowley Independent School District in Crowley, Tx.</p> <p>On information and belief, Huawei's United States Offices utilize the Huawei WLAN products to form a wireless local or metropolitan area network. These offices include Huawei Technologies USA, Inc. HQ's offices in Plano, Texas; Broomfield, CO; Houston, TX, Reston, VA; Philadelphia, PA; Irvine, CA; Cupertino, CA; Huawei Device USA, Inc. HQ's offices in Plano, Tx; Bellevue, WA; Mountain View, CA; Alpharetta, GA; Bridgewater, NJ; Santa Clara, CA; and San Diego, CA, as well as Futurewei Technologies, Inc.'s offices in Santa Clara, CA; Plano, TX, Bridgewater, NJ; Rolling Meadows, IL; Greensboro, NC; Louisville, CO; San Diego, CA; and Bellevue, WA.</p> <p><a href="https://www.huawei.com/us/contact-us#office">https://www.huawei.com/us/contact-us#office</a></p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**


'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION				
	<p>Further, in 2017, Huawei partnered with Cloud4Wi in San Francisco California to install its CloudCampus solution.</p> <p>See <a href="https://cloud4wi.com/cloud4wi-and-huawei/">https://cloud4wi.com/cloud4wi-and-huawei/</a></p> <p>Huawei CloudCampus solutions utilize various switches and access points, for example:</p> <div data-bbox="562 652 1705 1166"> <p style="text-align: center;"><b>To fully unlock the value of campus networks, you need these products</b></p> <table border="1"> <thead> <tr> <th data-bbox="590 734 1157 824">Switch</th><th data-bbox="1157 734 1698 824">WLAN</th></tr> </thead> <tbody> <tr> <td data-bbox="590 824 1157 1166"> <p>Fast deployment, secure and reliable easy O&amp;M, and agile innovation</p>  <p><b>S12700</b> Agile Switch</p> </td><td data-bbox="1157 824 1698 1166"> <p>All-scenario, customized Wi-Fi &amp; IoT integration</p> <div style="display: flex; justify-content: space-around;"> <div data-bbox="1024 943 1291 998">  <p><b>S5720-LI</b> Simplified Gigabit Ethernet Switch</p> </div> <div data-bbox="1415 935 1656 998">  <p><b>S5720-SI</b> Standard Gigabit Ethernet Switch</p> </div> </div> </td></tr> </tbody> </table> </div>	Switch	WLAN	<p>Fast deployment, secure and reliable easy O&amp;M, and agile innovation</p>  <p><b>S12700</b> Agile Switch</p>	<p>All-scenario, customized Wi-Fi &amp; IoT integration</p> <div style="display: flex; justify-content: space-around;"> <div data-bbox="1024 943 1291 998">  <p><b>S5720-LI</b> Simplified Gigabit Ethernet Switch</p> </div> <div data-bbox="1415 935 1656 998">  <p><b>S5720-SI</b> Standard Gigabit Ethernet Switch</p> </div> </div>
Switch	WLAN				
<p>Fast deployment, secure and reliable easy O&amp;M, and agile innovation</p>  <p><b>S12700</b> Agile Switch</p>	<p>All-scenario, customized Wi-Fi &amp; IoT integration</p> <div style="display: flex; justify-content: space-around;"> <div data-bbox="1024 943 1291 998">  <p><b>S5720-LI</b> Simplified Gigabit Ethernet Switch</p> </div> <div data-bbox="1415 935 1656 998">  <p><b>S5720-SI</b> Standard Gigabit Ethernet Switch</p> </div> </div>				




**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<div data-bbox="659 386 1398 1282"><p>CloudCampus Products and Solutions</p><p><b>Controller and analyzer</b></p><p>Agile CONTROLLER Campus Insight</p><p><b>Cloud managed modular switches</b></p><p>S12704 S12708 S12712</p><p><b>Flexible 8-48 port combinations, 88 switch models</b></p><p>Automatic 2.5G/5G/10G adaptation S6720-32C-PWH-SI</p><p>S5320/S5720 S6320/S6720 10GE switch</p><p><b>All series 23 indoor and outdoor AP models</b></p><p>802.11ax AP AP7000DN Indoor AP Dual 5G Outdoor AP8082DN Outdoor AP Agile distributed AP</p></div> <p><a href="https://e.huawei.com/en/material/onLineView?MaterialID=0b6395888b2a4bd49613a9bc28f3e95c">https://e.huawei.com/en/material/onLineView?MaterialID=0b6395888b2a4bd49613a9bc28f3e95c</a> at 15.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Further, Campus networks are an exemplary network that may work with Huawei eSight:</p>  <p>eSight Overview Presentation at 6.</p> <p>On information and belief, all Huawei WLAN products incorporate the Wireless Intrusion Detection System (WIDS) as described, for example in the WIDS and WIPS Technology White Paper:</p> <p align="center">“The Wireless Intrusion Detection System (WIDS) and Wireless Intrusion Prevention System (WIPS) functions monitor and prevent the preceding attacks on WLANs.</p> <p align="center">This document describes WIDS and WIPS technologies used by Huawei WLAN products.”</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 1.</p>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Huawei website currently lists the following WLAN products:</p>  <p>The screenshot shows the Huawei Enterprise website's WLAN product page. The left sidebar contains a navigation menu with categories like Products, Solutions, Industries, Technical Support, How to Buy, Partners, Resource Center, Training &amp; Certification, OpenLab, Community, and About Huawei Enterprise. The main content area is titled 'WLAN' and lists several product series under the heading 'Indoor Access Points':</p> <ul style="list-style-type: none"> <li><b>AP7000 Series:</b> AP7060DN Access Point, AP7052DE Access Point, AP7052DN &amp; AP7152DN Access Points.</li> <li><b>AP6000 Series:</b> AP6052DN Access Point, AP6060DN &amp; AP6160DN Access Points.</li> <li><b>AP5000 Series:</b> AP5510-Wi-Fi Access Point, AP5030DN &amp; AP5130DN Access Points.</li> <li><b>AP4000 Series:</b> AP4050DE-M Access Point, AP4050DN-E Access Point, AP4030TN Access Point, AP4051TN Access Point, AP4051DN &amp; AP4151DN Access Points, AP4030DN &amp; AP4130DN Access Points, AP4050DN HD Access Point, AP4050DN Access Point.</li> <li><b>AP2000 Series:</b> AP2051DN &amp; AP2051DN-E Access Points, AP2050DN-E Access Point, AP2051DN-S Access Point, AP2030DN Wall Plate Access Point, AP2050DN Access Point, AP2010DN Wall Plate Access Point.</li> </ul>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<div><div>Indoor Access Points</div><div><div>AP7000 Series</div><div><div>AP7060DN Access Point <small>new</small></div><div>AP7050DE Access Point</div></div><div>AP7052DE Access Point</div><div>AP7052DN &amp; AP7152DN Access Points</div></div><div><div>AP6000 Series</div><div><div>AP6052DN Access Point</div><div>AP6050DN &amp; AP6150DN Access Points</div></div></div><div><div>AP5000 Series</div><div><div>AP5510-W-GP Access Point <small>new</small></div><div>AP5030DN &amp; AP5130DN Access Points</div></div></div><div><div>AP4000 Series</div><div><div>AP4050DE-M Access Point <small>new</small></div><div>AP4050DN-E Access Point</div><div>AP4030TN Access Point</div></div><div><div>AP4051TN Access Point</div><div>AP4051DN &amp; AP4151DN Access Points</div><div>AP4030DN &amp; AP4130DN Access Points</div></div><div>AP4050DN-HD Access Point</div><div>AP4050DN Access Point</div></div><div><div>AP2000 Series</div><div><div>AP2051DN &amp; AP2051DN-E Access Points</div><div>AP2050DN-E Access Point</div></div><div>AP2051DN-S Access Point</div><div>AP2030DN Wall Plate Access Point</div><div>AP2050DN Access Point</div><div>AP2010DN Wall Plate Access Point</div></div><div><div>AP1000 series</div><div>AP1050DN-S Access Point</div></div></div>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<div><div><div><div><div><div>Outdoor Access Points</div><div>AP8082DN &amp; AP8182DN Access Points</div><div>AP8030DN and 8130DN Access Points</div></div><div><div>AP8050TN-HD Access Point</div><div>AP6510DN-AGN and AP6610DN-AGN 802.11n Outdoor Access Points</div></div><div><div>AP8050DN &amp; AP8150DN Access Points</div></div></div></div><div><div><div>Access Controllers</div><div>AC6805 Access Controller <div>new</div></div><div>AC6508 Access Controller <div>new</div></div><div>X1E Series Native Wireless Access Controller Card</div><div>S5730-HI Series Next- Generation Gigabit Agile Switches</div></div><div><div>AC6800V Access Controller</div><div>AC6005 Access Controller</div><div>ACU2 Wireless Access Controller Unit</div><div>S5720-HI Series Agile Fixed Switches</div></div><div><div>AC6605 Access Controller</div><div>AC6003 Access Controller</div><div>S6720-HI Series Full-Featured 10 GE Routing Switches</div></div></div></div><div><div><div>Scenario-specific product series</div><div>AD9431DN-24X Central Access Point</div><div>R240D &amp; R230D Remote Units</div><div>R450D Remote Unit</div></div><div><div>AD9430DN-24 Central Access Point</div><div>R251D &amp; R251D-E Remote Units</div><div>AP9131DN &amp; AP9132DN Access Points</div></div><div><div>AD9430DN-12 Central Access Point</div><div>R250D &amp; R250D-E Remote Units</div></div></div></div> <div><p><a href="https://e.huawei.com/us/products/enterprise-networking/wlan">https://e.huawei.com/us/products/enterprise-networking/wlan</a> (as of March 13, 2019).</p><p>See also, e.g., Huawei Access Point Datasheets (“Rogue device monitoring Huawei APs support WIDS/WIPS, and can monitor, identify, defend, counter, and perform refined management on the rogue devices, to provide security guarantees for air interface environment and wireless data transmission.”) On information and belief, all APs support WIDS, see also, e.g., AP2030DN at 2; AP4050DN-E at 3; AP4051DN &amp; AP4151DN at 3; AP8050DN &amp; AP8150DN at 3; AP6052DN at 4; AP6050DN&amp;AP6150DN at 4.</p></div>



***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p><i>See also</i>, Huawei Enterprise AP Series 802.11ac Brochure:</p> <p>For enterprise networks of different types and scales, Huawei offers the following AP models:</p> <p>802.11ac indoor 7X30 series and 5X30 series APs, outdoor 802.11ac 8X30 series APs, and 802.11ac AP9130DN vehicle-mounted APs specially designed for rail transit communications.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT  
CLAIM 12

INFRINGEMENT BY HUAWEI CORPORATION

Table 5-2 Features of Huawei 802.11ac APs

Huawei 802.11ac AP	AP5030DN/ AP5130DN	AP7030DE	AP8030DN/ AP8130DN	AP9130DN
Target market	Mid-range market: small- to medium-sized enterprises	High-end market: medium- to large-sized enterprises	Large campus outdoor coverage or backhaul	Rail transit
Working mode	Fit/Fat AP	Fit AP	Fit/Fat AP	Fat AP
Dying gasp	-	✓	✓	✓
Wireless positioning/ Real-Time Location System (RTLS)	✓	✓	✓	-
Spectrum analysis	✓	✓	✓	-
Seamless roaming	✓	✓	✓	✓
IPv6	✓	✓	✓	✓
Wireless Intrusion Prevention System (WIPS)/Wireless Intrusion Detection System (WIDS)	✓	✓	✓	✓

Huawei Routers deployed in a WLAN have various other security mechanisms, including:  
  
“3.2.4 Security

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>...</p> <p>NAC</p> <p>Network Admission Control (NAC) is an end-to-end access security framework and includes... MAC address authentication”</p> <p>Huawei AR120&amp;AR150&amp;AR160&amp;AR200&amp;AR500&amp;AR510&amp;AR1 200&amp;AR2200&amp;AR3200&amp;AR3600 Series Enterprise Routers Product Description, Issue 05 (2016-06-15) at 43.</p> <p>Routers may further operate as an Access Controller and provides MAC address authentication for WLAN:</p> <p>“3.2.6 WLAN</p> <p>A wireless local area network (WLAN) connects two or more computers or devices and enables the devices to communicate by using the wireless telecommunication technology. WLAN uses the wireless technology to implement fast Ethernet access. The primary advantage of WLAN is that terminals, such as computers, can access a network through a wireless medium rather than a physical cable. This facilitates network construction and allows users to move around without interrupting communication. WLAN is more flexible than traditional wired access.</p> <p>WLAN is widely used in public areas such as on campuses, business centers, and airports. The WLAN uses cables at the backbone layer, and users access the WLAN through one or more access points (APs) using radio waves. The transmission distance of an AP is tens of meters.</p> <p>IEEE 802.11 is widely used by WLANs. The device can function as an access controller (AC) or a Fat access point (FAT AP). The device as the AC or Fat AP supports 802.11a, 802.11b, 802.11g, 802.11an, and 802.11n.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>NOTE</p> <p>Only AR121W, AR129W, AR121GW-L, AR129GW-L, AR151W-P, AR156W, AR157W, AR157VW, AR158EVW, AR161W, AR161FGW-L, AR169W, AR161FW-P-M5, AR161FGW-La, AR169FVW, AR169FGVW-L, AR169FGW-L, AR169W-P-M9, AR169RW-P-M9, AR201VW-P, AR207VW, AR510 series, AR503GW-LM7, AR503GW-LcM7, AR1220W, AR1220EVW and AR1220VW support WLAN-FAT AP.</p> <p>The device supports the following WLAN features:</p> <ul style="list-style-type: none"> <li>- WLAN user management</li> <li>- Dot1X access authentication</li> <li>- MAC address authentication</li> <li>- Pre-share-key (PSK) authentication</li> <li>- EAPOL-Key negotiation</li> <li>- User access control</li> <li>- AAA for WLAN users</li> </ul> <p>Huawei AR120&amp;AR150&amp;AR160&amp;AR200&amp;AR500&amp;AR510&amp;AR1 200&amp;AR2200&amp;AR3200&amp;AR3600 Series Enterprise Routers Product Description, Issue 05 (2016-06-15) at 47.</p> <p><i>See also, e.g., Huawei Remote Unit Datasheets: R450D at 6 (“Security features - WIDS including rogue AP and STA detection, attack detection, STA/AP blacklist and whitelist... -Intrusion prevention”); R251D &amp; R251D-E (“Wireless intrusion detection system (WIDS) and wireless intrusion prevention system (WIPS), including rogue device detection and countermeasure, attack detection and dynamic blacklist, and STA/AP blacklist and whitelist”)</i></p> <p>Huawei consumer devices, including laptops, phones and tablets, are also designed to communicate with wireless networks via the IEEE 802.11 protocols.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>The Huawei eSight and eSight Network further incorporates the WIDS system:</p> <p style="padding-left: 40px;">Wireless Network Security Detection</p> <p style="padding-left: 40px;">The Wireless Intrusion Detection System (WIDS) monitors intrusion devices and non-Wi-Fi interferences and provides frequency spectrum analysis features.</p> <p style="padding-left: 40px;">WIDS management: The WIDS manages wireless network interferences in different categories. Interferences are classified based on user customized rules. Upon detecting an interference, the WIDS chooses whether to generate an alarm based on user alarm configurations. The WIDS can also take countermeasures for unauthorized devices.</p> <p>Huawei eSight Full Product Datasheet, CH 12 eSight WLAN Manager; p. 53 (2013-09-03) Huawei Technologies Co., Ltd.; <i>see also</i> eSight V300R007C00 Product Description, Issue 09 (2018-02-08) at p. 58-59 (indicating that, on information and belief, all versions of eSight incorporate WIDS).</p> <p>In another non-limiting example, Huawei installed a Wireless local or metropolitan area network at Weichai in Chicago, Illinois using S9700/S6700/S5700/WLAN products:</p> <p style="padding-left: 40px;">The [Weichai North America] center located in suburban Chicago, which covers 20-acre parcel, and over 300 engineers will be working in this center.</p> <p style="padding-left: 40px;">...</p> <p style="padding-left: 40px;">Huawei offered a comprehensive and tailor-made solution for Weichai, which provided end-to-end applications and services based on Huawei products [including] Two clustered S9706 LAN switches stacking with service interfaces at core layer combined with stacked gigabyte access S5700 POE LAN switches to create a loop-free network with high reliability.</p>



***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<ul style="list-style-type: none"> <li>• High density wireless users access capability and intelligent wireless network</li> </ul> <p>The Huawei AP6010 LAN access points provide integrated built-in MIMO antenna and spectrum analysis for even frequency coverage with no coverage hole, concurrent user access rate 20 percents higher than industry average. Moreover, wireless authentication and authorization can provide fine-grained access control for the security of WLAN network.</p> <p>...</p> <p>Huawei was chosen as the only vendor by Weichai...</p> <p>...</p> <p>Huawei provided the necessary infrastructure of networks, Unified Communications and Collaboration (UC&amp;C), IT solutions and simplified network management.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Huawei In Large Enterprise Case Studies at 12-13 (available at <a href="http://www.enterprisesolutions.altech.co.za/sites/">http://www.enterprisesolutions.altech.co.za/sites/</a>).</p> <div data-bbox="611 436 1572 997" data-label="Image"> </div> <p><a href="#">collab_d7_live/files/Huawei_in_Large_Enterprise%28include%20Small%20Campus%29_1.pdf</a>)  HUAWEI WLAN Successful Stories PowerPoint at 2.</p> <p>Huawei further installed networks at Crowley Independent Schools in Texas:</p> <p>HUAWEI WLAN Successful Stories PowerPoint at 4; <i>see also</i>  <a href="http://support.huawei.com/en/about/media_center/video_clips_list/hw-341648.htm">http://support.huawei.com/en/about/media_center/video_clips_list/hw-341648.htm</a></p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**


'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<div data-bbox="583 396 1671 1016" data-label="Complex-Block"> <p style="text-align: right; font-size: small;">HUAWEI ENTERPRISE ICT SOLUTIONS A BETTER WAY</p> <h3 style="color: red;">Crowley Independent School District in USA</h3> <div style="display: flex;"> <div style="flex: 1;"> <p><b>Background &amp; Requirement</b></p> <ul style="list-style-type: none"> <li>■ Crowley Independent School District is a public school district based in Crowley, Texas.</li> <li>■ Serves the high/middle/elementary schools based in Crowley/Portions of Fort Worth and Edgecliff Village.</li> </ul> <p><b>Huawei Solution</b></p> <ul style="list-style-type: none"> <li>■ Huawei AP6010DN-AGN provide at most 600Mbps wireless connection for the students and teachers connect to CISD campus network.</li> <li>■ Huawei AC6605 can support at most 512 APs management per AC, provide a high expandable WLAN network for CISD schools.</li> <li>■ The Related Products: AC6605/AP6010DN</li> </ul> <p><b>Benefits</b></p> <ul style="list-style-type: none"> <li>■ Multiple terminal wireless access, compatible of different kinds of terminals, provide fast and reliable access through ISD WLAN network.</li> <li>■ Advance Wireless Structure: Distributed AP deploy and centralized management reduce the OPEX of the school's IT system.</li> </ul> </div> <div style="flex: 1;">  </div> </div> <p style="font-size: x-small;">enterprise.huawei.com • Huawei Confidential • 4</p> <p style="text-align: right;"> <b>HUAWEI</b></p> </div> <p>On information and belief, and as further discovery will show, Huawei has installed networks in other US locations, for example:</p> <p style="margin-left: 40px;">Sears, one of the leading US retail enterprises, decided to use Huawei's technology and equipment when upgrading the networks of hundreds of stores. Northern Michigan University, Crowley Independent School District in Texas and Digital Domain, a visual effects and digital production company in Hollywood, have adopted storage, Internet solutions and other services provided by Huawei.</p>



**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p><a href="http://www.globaltimes.cn/content/864994.shtml">http://www.globaltimes.cn/content/864994.shtml</a></p> <p>On information and belief, all Huawei WLAN products, when combined to form a wireless local or metropolitan area network, are able to utilize the WIDS/WIPS technology. Huawei WLAN products are specifically designed to be linked together to form a wireless network, and to be used with other laptops, tablets, phones and WiFi capable devices, and Huawei directs and encourages such conduct. Accordingly, Huawei indirectly infringes this claim by inducing infringement.</p> <p>See e.g., WLAN Installation Service, available at <a href="http://support.huawei.com/enterprise/NewsReadAction.action?newType=05&amp;contentId=NEWS1000006056">http://support.huawei.com/enterprise/NewsReadAction.action?newType=05&amp;contentId=NEWS1000006056</a>; Enterprise NMS and Application Software Installation Service, available at <a href="http://support.huawei.com/enterprise/NewsReadAction.action?newType=05&amp;contentId=NEWS1000006040">http://support.huawei.com/enterprise/NewsReadAction.action?newType=05&amp;contentId=NEWS1000006040</a> and other channel partner service descriptions at <a href="https://e.huawei.com/en/partner/partner-program/services">https://e.huawei.com/en/partner/partner-program/services</a></p> <p>In yet a further example, Huawei has a 3, 4 and 5 Star and Global Certified Service Partner Certification program, in which, among other things, allows partners to receive Partner Enablement Support from Huawei. Service partners must meet certain requirements, for example:</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<div data-bbox="600 418 1157 1170"><p><b>Certification Requirement</b></p><ul style="list-style-type: none"><li>• HCNA x 2</li><li>• Domain:<ul style="list-style-type: none"><li>Enterprise Networking (R&amp;S, WLAN, and Security), or</li><li>Enterprise Networking (Transmission and Access), or</li><li>Enterprise Cloud Communications (UC, CC, VC, and IVS), or</li><li>IT (Storage, Server, Cloud Computing, and DC), or</li><li>Network Energy (DCF and UPS)</li></ul></li></ul></div> <p data-bbox="447 1252 1304 1279"><a href="https://e.huawei.com/en/partner/partner-program/Overview/Standard">https://e.huawei.com/en/partner/partner-program/Overview/Standard</a></p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Huawei offers its partners numerous trainings and certificates related to Enterprise Network, including courses that train individuals on designing and deploying WLAN networks, including aspects of WIDS/WIPS and network security.</p> <p>See, e.g., Training Description for Enterprise Network, available at <a href="https://e.huawei.com/en/marketing-material/partner-document/partner/en/channel%20partner%20program/legal%20-%20commercial/services/learning%20services/hw_201676">https://e.huawei.com/en/marketing-material/partner-document/partner/en/channel%20partner%20program/legal%20-%20commercial/services/learning%20services/hw_201676</a>; see also <a href="https://e.huawei.com/en/partner/partner-program/apply-for-specialization/network">https://e.huawei.com/en/partner/partner-program/apply-for-specialization/network</a>; see also <a href="https://e.huawei.com/en/partner/partner-program/Overview/Enablement">https://e.huawei.com/en/partner/partner-program/Overview/Enablement</a> (“Huawei’s Training System Huawei offers a broad variety of training courses such as HALP training, e-learning, and instructor-led courses to help channel partners improve their capabilities.”)</p> <p style="padding-left: 40px;">Huawei has at least 11 service partners that are part of its Enterprise Networking CSP Program, including:</p> <p style="padding-left: 40px;">Eccom Network(USA) Inc  FusionStorm  China Telecom (Americas) Corporation  Datalink Networks, Inc.  Entisys360  Vlan24 Inc  CANCOM US  UNeed Solutions Inc. dba Noviant  MJP Technologies Inc  Unified Connexions, Inc.  Stellar Services</p> <p>See <a href="https://e.huawei.com/en/partner/find-a-partner">https://e.huawei.com/en/partner/find-a-partner</a></p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Huawei encourages its partners to “promote Huawei’s brand in the enterprise business market.”:</p> <div data-bbox="592 451 1333 1058"> <pre> graph TD     Huawei[<b>Huawei</b>] --&gt; GDD[GD/RD/Distributor]     Huawei --&gt; GP[VAP]     GDD --&gt; Gold((Gold))     GDD --&gt; Silver((Silver))     GDD --&gt; Auth((Authorized))     GP --&gt; GPBox[GP/RP/VAP]     Gold --&gt; EndUser[End User]     Silver -.-&gt; DP[Downstream Partners]     Auth -.-&gt; DP     GPBox --&gt; DP     DP -.-&gt; EndUser     </pre> <p>The diagram illustrates Huawei's channel policy. At the top is a red box labeled 'Huawei'. Two arrows point down from 'Huawei' to a grey box labeled 'GD/RD/Distributor' and a white box labeled 'GP/RP/VAP'. From 'GD/RD/Distributor', three arrows point down to three grey circles labeled 'Gold', 'Silver', and 'Authorized'. From 'GP/RP/VAP', an arrow points down to a white box labeled 'GP/RP/VAP'. From the 'Gold' circle, an arrow points down to a grey bar at the bottom labeled 'End User'. From the 'Silver' and 'Authorized' circles, dashed arrows point down to a white box labeled 'Downstream Partners'. From the 'GP/RP/VAP' box, an arrow points down to 'Downstream Partners'. From 'Downstream Partners', dashed arrows point down to the 'End User' bar.</p> </div> <p>Huawei’s Channel Policy Principles</p> <p>The principle of Huawei’s channel policy is “to work and collaborate on a win-win basis.”</p> <p>Work and collaborate: Maximize the value for our channel partners and customers by motivating channel partners to explore the market and promote Huawei’s brand in the enterprise business market.</p>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Classification of Channel Partners</p> <p>Tier1 Partner: Distributor and Value Added Partner (VAP). Distributors include Global Distributors (GDs), Regional Distributors (RDs), and Local Distributors. Global Distributors and Regional Distributors are distributors that run business in multiple countries.</p> <p>Global Partners (GPs) and Regional Partners (RPs) work with Huawei in multiple countries and regions.</p> <p>Tier 2 Partner: Gold Partner, Silver Partner, and Authorized Partner</p> <p>For more information visit our Channel Partner Program page.</p> <p><a href="https://e.huawei.com/en/partner/become-a-partner">https://e.huawei.com/en/partner/become-a-partner</a></p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<div data-bbox="590 386 1549 776"> <p align="center"><b>Huawei Channel Structure</b></p> <pre> graph LR     Huawei[HUAWEI ICT Products &amp; Solutions] --&gt; GP[GP Global Partner]     Huawei --&gt; RP[RP Regional Partner]     Huawei --&gt; VAP[VAP Value-added Partner]     Huawei --&gt; GD[GD Global Distributor]     Huawei --&gt; RD[RD Regional Distributor]     Huawei --&gt; Distributor[Distributor]     GP --&gt; EndUser[End User]     RP --&gt; EndUser     VAP --&gt; EndUser     GD --&gt; Gold[Gold]     GD --&gt; Silver[Silver]     GD --&gt; Authorized[Authorized]     RD --&gt; Gold     RD --&gt; Silver     RD --&gt; Authorized     Distributor --&gt; Gold     Distributor --&gt; Silver     Distributor --&gt; Authorized     Gold --&gt; EndUser     Silver --&gt; EndUser     Authorized --&gt; EndUser     </pre> </div> <p>Distributors must have “3 dedicated employees for Huawei enterprise business” and 6M sales performance thresholds Channel Partner Program Briefing 2018, available at <a href="https://e.huawei.com/en/marketing-material/partner-document/partner/en/policy/20170428113204">https://e.huawei.com/en/marketing-material/partner-document/partner/en/policy/20170428113204</a></p> <p>Further Distributors</p> <ul style="list-style-type: none"> <li>- Act as major partners of Huawei’s Enterprise Business Group (BG) in regional markets.</li> <li>- Promise to accomplish business targets for related products and targets for distribution business.</li> </ul> <p><a href="https://e.huawei.com/en/partner/partner-program/policy">https://e.huawei.com/en/partner/partner-program/policy</a></p> <p>At least two Huawei Distributors exist in the United States,</p>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>ASI Computer Technologies, Inc. in Fremont, CA; (selling Enterprise Cloud Communications, Data Center Switch, IT, Cloud Computing, Transport Network, Security, Access Network, Video Surveillance, Enterprise Networking Common, Campus Switch &amp; WLAN, Enterprise Gateway, Router, UPS, Network Management )</p> <p>Wav, Inc. in Aurora Ill, (selling Data Center Switch, Enterprise Gateway, IT, Cloud Computing, Access Network, Network Management, Video Surveillance, Router, Enterprise Networking Common, Enterprise Cloud Communications, UPS, Campus Switch &amp; WLAN, Transport Network, Security)</p> <p><a href="https://e.huawei.com/en/partner/find-a-partner">https://e.huawei.com/en/partner/find-a-partner</a></p> <p>Value Added Partners must have a 2M sales performance threshold  Channel Partner Program Briefing 2018, at p. 6, available at <a href="https://e.huawei.com/en/marketing-material/partner-document/partner/en/policy/20170428113204">https://e.huawei.com/en/marketing-material/partner-document/partner/en/policy/20170428113204</a></p> <p>Value Added Partners:</p> <ul style="list-style-type: none"> <li>- Act as major partners of Huawei's Enterprise BG in regional markets.</li> <li>- Promise to attain business targets for related industries and customers of Huawei's Enterprise BG.</li> <li>- Develop industry customer relationship platforms and provide support for Huawei's products to industry users.</li> </ul> <p><a href="https://e.huawei.com/en/partner/partner-program/policy">https://e.huawei.com/en/partner/partner-program/policy</a></p> <p>Value Added Partners in the United States that offer Enterprise Network products include:</p>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**


'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Proyectos Integrales Solares SL dba Proinso US LLC  FusionStorm  Consolidated Electrical Distri  Rahi Systems, Inc  Onesource Distributors, LLC  Sonepar Management Us, Inc.  CANCOM US  WORLD WIDE TECHNOLOGY, LLC  Wesco Distribution, Inc.  Entisys360  China Telecom (Americas) Corporation</p> <p>See <a href="https://e.huawei.com/en/partner/find-a-partner">https://e.huawei.com/en/partner/find-a-partner</a></p> <p>Gold Partners in the United States that offer Enterprise Network products include  Cloud Trekkers Technologies Inc</p> <p>Silver Partners in the United States that offer Enterprise Network products include  Twotrees Technologies, LLC  Mark III Systems, Inc  UNeed Solutions Inc. dba Noviant</p> <p>Gold and Silver Partners have sales performance thresholds of 0.5M and 0.25M (Channel Partner Program Briefing 2018, at p. 6, available at <a href="https://e.huawei.com/en/marketing-material/partner-document/partner/en/policy/20170428113204">https://e.huawei.com/en/marketing-material/partner-document/partner/en/policy/20170428113204</a></p>



***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Gold and Silver Partners</p> <ul style="list-style-type: none"> <li>- Act as major partners of Huawei's Enterprise BG in regional markets.</li> <li>- Promise to accomplish business targets for related industries and customers of Huawei's Enterprise BG.</li> <li>- Develop industry customer relationship platforms and provide support for Huawei's products to industry users.</li> </ul> <p><a href="https://e.huawei.com/en/partner/partner-program/policy">https://e.huawei.com/en/partner/partner-program/policy</a></p> <p>Huawei also has more than 50 Authorized Partners that offer Enterprise Network products  See <a href="https://e.huawei.com/en/partner/find-a-partner">https://e.huawei.com/en/partner/find-a-partner</a></p> <p>Huawei further actively encourages infringement and sales of Huawei networks by imposing penalties for violations:</p> <p style="padding-left: 40px;">“Level-2 violation” of the partnership agreement to “direct unauthorized sales”</p> <p style="padding-left: 40px;">“Level-3 violation” for “indirect unauthorized sales” and if a “Channel does not fulfill service contract or order” or “Provides services to customers through non-Huawei certified maintenance companies”</p> <p>Channel Partner Program Briefing 2018 at p.9, available at <a href="https://e.huawei.com/en/marketing-material/partner-document/partner/en/policy/20170428113204">https://e.huawei.com/en/marketing-material/partner-document/partner/en/policy/20170428113204</a></p>


**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
<p><b>[a]</b> a plurality of stations for transmitting data therebetween using a media access layer (MAC), each of said stations having a respective MAC address associated therewith; and</p>	<p>Huawei '678 Patent Accused Products form a network comprising a plurality of stations (including, without limitation, Stations, STAs, Access Points, APs, and/or Remote Units) for transmitting data therebetween using a media access layer (MAC), each of said stations having a respective MAC address associated therewith.</p> <p>One exemplary network configuration is shown:</p>  <p>The diagram, titled 'WLAN Infrastructure' and 'Figure 1-1 WLAN Networking', illustrates three network topologies. At the top, a 'RADIUS Server' and 'NMS' are connected to a central 'MAN' (Management and Network) cloud. Below this, three distinct network configurations are shown, each enclosed in a dashed box:</p> <ul style="list-style-type: none"> <li><b>Chain networking (tunnel forwarding):</b> This topology shows a central 'AC' (Access Controller) connected to an 'Aggregation switch'. The 'Aggregation switch' is connected to an 'Access switch', which in turn is connected to two 'AP' (Access Points). A 'CAPWAP tunnel' is shown between the 'AC' and the 'Aggregation switch'. Data flow is indicated by a blue arrow from the 'APs' through the 'Access switch' and 'Aggregation switch' to the 'AC'. Management flow is indicated by a red dashed arrow from the 'APs' through the 'Access switch' and 'Aggregation switch' to the 'AC'.</li> <li><b>Chain networking (direct forwarding):</b> This topology shows a central 'AC' connected to an 'Aggregation switch'. The 'Aggregation switch' is connected to an 'Access switch', which is connected to two 'APs'. A 'CAPWAP tunnel' is shown between the 'AC' and the 'Aggregation switch'. Data flow is indicated by a blue arrow from the 'APs' through the 'Access switch' and 'Aggregation switch' to the 'AC'. Management flow is indicated by a red dashed arrow from the 'APs' through the 'Access switch' and 'Aggregation switch' to the 'AC'.</li> <li><b>Branched networking (direct forwarding):</b> This topology shows a central 'AC' connected to an 'Aggregation switch'. The 'Aggregation switch' is connected to an 'Access switch', which is connected to two 'APs'. A 'CAPWAP tunnel' is shown between the 'AC' and the 'Aggregation switch'. Data flow is indicated by a blue arrow from the 'APs' through the 'Access switch' and 'Aggregation switch' to the 'AC'. Management flow is indicated by a red dashed arrow from the 'APs' through the 'Access switch' and 'Aggregation switch' to the 'AC'.</li> </ul>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>As shown in Figure 1-1, a WLAN consists of access points (APs), PoE switches, access controllers (ACs), Remote Authentication Dial In User Service (RADIUS) server, and network management system (NMS).</p> <ul style="list-style-type: none"> <li>- AP: WLAN access device. Huawei provides a series of fit APs to meet indoor and outdoor networking requirements.</li> <li>- PoE switch: upstream devices for APs. It provides data switching and power for APs. If only one AC is required and the AC has PoE ports, the PoE switch is not required.</li> <li>- AC: manages APs and controls the rights of WLAN users.</li> <li>- RADIUS server: authenticates WLAN users and assigns rights to them. The RADIUS server is installed on the SPES server.</li> <li>- NMS: manages APs and ACs. It monitors status of ACs and APs in real time, processes alarms, and analyzes data.</li> </ul> <p>HUAWEI WLAN Typical Configuration Examples, Issue 01 (2017-12-29) at 2.  <a href="https://support.huawei.com/enterprise/en/doc/EDOC1000184389/1d542042/introduction-to-wlan">https://support.huawei.com/enterprise/en/doc/EDOC1000184389/1d542042/introduction-to-wlan</a></p> <p>In another configuration example, a WDS (Wireless Distribution System) may wirelessly connect two WLANs:</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p><b>Figure 1-1 WDS network</b></p>  <p>The diagram illustrates a Wireless Distribution System (WDS) network. It features three Access Points (APs) connected in a chain: AP3 (leaf), AP2 (middle), and AP1 (root). These APs are connected via a dashed line labeled 'WDS network'. A central Access Controller (AC) is connected to AP1. A Switch is connected to AP3 and an L2 network. Several Station (STA) devices are shown connected to the APs. A legend at the bottom indicates that yellow lightning bolts represent 'WVL' (Wireless Virtual Link) and grey lightning bolts represent 'Service VAP' (Service Virtual Access Point).</p> <p>Huawei Technologies Co., Ltd. WLAN WDS Technology White Paper Issue 03 (2017-11-21) at 1-2.</p>


**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p><i>See also:</i></p> <div data-bbox="638 428 1541 1192"> <p align="center"><b>Figure 4-7 Networking for configuring rogue device detection and containment</b></p> </div> <p>HUAWEI WLAN Typical Configuration Examples, Issue 01 (2017-12-29) at 123.</p>


**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>On WLANs, APs, STAs, ad hoc devices, and wireless bridges need to be monitored. When an AP working in normal mode with air interface scan functions enabled on radios or in monitor mode, it can identify the types of neighboring wireless devices based on detected 802.11 management and data frames. The wireless device identification process is as follows:</p> <ol style="list-style-type: none"> <li>1. On the AC, the AP is configured to work in monitor mode or in normal mode with air interface scan functions enabled on radios.</li> <li>2. The AC delivers the configuration to the AP.</li> <li>3. The AP scans channels to collect information about neighboring wireless devices, and listens on frames sent by neighboring wireless devices to identify device types. The AP listens on the following types of frames: <ul style="list-style-type: none"> <li>– Beacon</li> <li>– Association Request</li> <li>– Association Response</li> <li>– Reassociation Request</li> <li>– Reassociation Response</li> <li>– Probe Response</li> <li>– Data frame</li> </ul> </li> <li>4. The AP reports the identified device types to the AC. The AC then determines whether the identified devices are authorized and notifies the AP of rogue devices.</li> </ol> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 4.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p style="text-align: center;"><b>Figure 2-3 Rogue device detection and identification</b></p>  <p>The AP identifies the types of neighboring wireless devices based on detected 802.11 management and data frames.</p> <p>The <b>Frame Control</b> field in the MAC header of a frame indicates the frame type. Figure 2-4 shows the subfields of the <b>Frame Control</b> field.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION				
	<p style="text-align: center;"><b>Figure 2-4 MAC header of an 802.11 frame</b></p>  <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 5.</p> <p>Each station has a MAC address associated therewith</p> <table border="1" data-bbox="600 1057 1812 1198"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>MAC address</td><td>MAC address of the device</td></tr> </tbody> </table> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 9.</p>	Attribute	Description	MAC address	MAC address of the device
Attribute	Description				
MAC address	MAC address of the device				



**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>MAC address - A link layer address or physical address. It is six bytes long.</p> <p><i>See e.g., eSight V300R007C00 Product Description, Issue 09 (2018-02-08) at 253.</i></p>
<p><b>[b]</b> a policing station for detecting intrusions into the wireless network by</p>	<p>Huawei '678 Patent Accused Products comprise a policing station for detecting intrusions into the wireless network.</p> <p>For example, Huawei WLAN products utilize the WIDS technology to detect intrusions</p> <p>802.11 networks are open wireless public networks, and vulnerable to various threats caused by unauthorized APs and STAs, ad hoc networks, bogus APs, and denial of service (DoS) attacks of malicious STAs. The Wireless Intrusion Detection System (WIDS) and Wireless Intrusion Prevention System (WIPS) functions monitor and prevent the preceding attacks on WLANs.</p> <p>This document describes WIDS and WIPS technologies used by Huawei WLAN products. Enterprises can use the WIDS and WIPS functions to secure their wireless networks, reduce interference from unauthorized devices, protect STAs from malicious attacks, and deliver better user experience.</p> <p>...</p> <p>The WIDS detects rogue STAs, malicious user attacks, and wireless network intrusions.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 1-2.</p> <p>The WIDS and WIPS functions of Huawei WLAN products ensure security of customers' wireless networks, reduce interference from rogue devices, and protect STAs from malicious attacks, delivering better user experience.</p>


**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<ul style="list-style-type: none"> <li>● Selection of different protection measures based on their network scale</li> </ul> <p>The WIDS and WIPS functions provide different protection measures based on the scale of customer networks.</p> <p>- For home networks or small enterprise networks, protection measures are provided to control access of APs and STAs using blacklists and whitelists.</p> <p>- For small- and medium-scale enterprise networks, WIDS attack detection and defense are provided.</p> <p>- For medium- and large-scale enterprise networks, rogue device detection, identification, defense, and containment are provided.</p> <p>Customers can also perform other protection configurations.</p> <ul style="list-style-type: none"> <li>● Rogue device identification and defense</li> </ul> <p>The WIDS and WIPS functions can identify rogue devices on the WLAN and take preventive measures to protect customer networks against intrusions or interference of rogue devices.</p> <ul style="list-style-type: none"> <li>● Customer network protection against attacks</li> </ul> <p>The WIDS and WIPS functions can detect multiple types of attacks such as flood attacks, weak IV attacks, spoofing attacks, brute force WPA/WPA2/WAPI PSK cracking, and WEP shared key cracking. The functions protect customer networks from being attacked by rogue devices.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 20.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>For example, a monitor AP may act as a policing station for detecting intrusions (e.g., rogue devices) into the wireless network:</p> <div data-bbox="735 561 1432 1237" data-label="Diagram"> <p style="text-align: center;"><b>Figure 2-1 Overview of WLAN security technologies</b></p> <p>The diagram illustrates the components and interactions in a WLAN security system. At the top, four icons represent the main entities: STA (Station), AP (Access Point), AC (Access Controller), and AAA server (Authentication, Authorization, and Accounting server). Below these icons, several interaction arrows are shown: a large double-headed arrow between STA and AC labeled 'Access authentication'; a double-headed arrow between STA and AP labeled 'Link encryption'; a dashed arrow from AAA server to AC labeled 'Policy control'; and two red double-headed arrows between AP and AC labeled 'Attack detection and defense' and 'Rogue device detection and containment'. To the right of these red arrows, the text 'WIDS &amp; WIPS' is written twice. At the bottom left, there are icons for a laptop, two small orange squares, and a signal wave, with an arrow pointing from the laptop towards the AP.</p> </div>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<div data-bbox="562 386 1560 695" style="border: 1px solid black; padding: 10px; margin: 10px auto; width: 80%;"> <p>In the preceding figure, the WIDS and WIPS are used to detect and contain rogue devices respectively. The WIDS can detect rogue APs, rogue wireless bridges, rogue STAs, ad hoc devices, and interference APs with duplicate channels. The WIPS can disassociate authorized STAs from rogue APs, and disconnect rogue STAs and ad hoc devices from the WLAN to contain rogue devices.</p> <p> <b>NOTE</b>  APs in this document are Fit APs. Fat APs and cloud APs also provide the WIDS and WIPS functions. Different from Fat APs that provide the WIDS and WIPS functions themselves, Fit APs need to work with ACs to provide the functions.</p> </div> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 3.</p> <p>2.2 Rogue Device Detection</p> <p>Rogue device detection of WLANs is enabled to monitor the entire network. Monitor APs are deployed on a WLAN that needs protection to monitor the entire network. The monitor APs can periodically listen on wireless signals to detect rogue devices.</p> <p>2.2.1 Working Modes of APs</p> <p>Before enabling rogue device detection on a WLAN, configure APs' working modes.</p> <p>An AP works in normal or monitor mode.</p> <ul style="list-style-type: none"> <li>• Normal mode: If the WIDS and WIPS functions and other air interface scan functions are disabled on a radio, such as spectrum analysis and STA location, this radio can be used only to transmit common WLAN service data. If the WIDS and WIPS functions</li> </ul>


**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>are enabled, the working mode of the radio is automatically switched to hybrid. In addition to transmitting common WLAN service data, the radio can also provide the monitoring function. In this case, transmission of common WLAN service data is affected.</p> <ul style="list-style-type: none"> <li>Monitor mode: A monitor AP scans devices on the WLAN and listens on all 802.11 frames on wireless channels. In this case, the monitor AP provides only the monitoring function and cannot transmit WLAN service data.</li> </ul> <p>The following figure shows the principles of the two working modes.</p> <div data-bbox="720 748 1501 1128" data-label="Diagram"> <p><b>Normal mode</b></p> <p>The WISD and WIPS functions and other air interface scan functions are disabled.</p> <p>Channel</p> <p>The WISD and WIPS functions are enabled.</p> <p>Channel Ch1 Channel Ch2 ... Channel ChN</p> <p>Monitoring period</p> <p><b>Monitor mode</b></p> <p>Channel Ch1 Channel Ch2 Channel Ch3 ... ChN Channel Ch1 Channel</p> <p>Long monitoring period: <math>N \times</math> Monitoring period for each channel  (<math>N</math> indicates the number of monitored channels.)</p> </div> <p>Figure 2-2 Principles of the two working modes</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

**'678 PATENT  
CLAIM 12**

**INFRINGEMENT BY HUAWEI CORPORATION**



Huawei Technologies Co., Ltd. *WLAN WIDS & WIPS Technology White Paper*; Issue 2.0 (2017-07-05) at 3-4.

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>The device information reporting process is described as follows:</p> <ul style="list-style-type: none"> <li>• On the AC, a short interval is configured for the AP to report information about neighboring wireless devices. (The long interval is provided by the system by default.)</li> <li>• The AC delivers the configuration to the AP.</li> <li>• The AP listens on frames to collect information about neighboring wireless devices, and reports the information to the AC at the specified short interval. The AC then determines whether the wireless devices are rogue devices and delivers the identification result to the AP. When the wireless devices are scanned again by the AP, the AP automatically checks whether they are rogue devices based on the identification result sent by the AC.</li> <li>• The AP reports full information about all detected wireless devices to the AC at the long interval for information synchronization. The AC then determines whether the wireless devices are rogue devices and delivers the identification result to the AP. When the wireless devices are scanned again by the AP, the AP automatically checks whether they are rogue devices based on the identification result sent by the AC.</li> </ul> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 8.</p>


**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

**'678 PATENT  
CLAIM 12**

**INFRINGEMENT BY HUAWEI CORPORATION**

The following figure shows the WIDS attack defense process.

**Figure 2-14 WIDS attack defense**



Huawei Technologies Co., Ltd. *WLAN WIDS & WIPS Technology White Paper*; Issue 2.0 (2017-07-05) at 17.



***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>The Huawei eSight Platform, including at least the WLAN Manager and LogCenter Manager, is further used as a network management system that also detects intrusions into the wireless network:</p> <p>The Huawei eSight Platform further incorporates the WIDS system:</p> <p style="padding-left: 40px;">Wireless Network Security Detection</p> <p style="padding-left: 40px;">The Wireless Intrusion Detection System (WIDS) monitors intrusion devices and non-Wi-Fi interferences and provides frequency spectrum analysis features.</p> <p style="padding-left: 40px;">WIDS management: The WIDS manages wireless network interferences in different categories. Interferences are classified based on user customized rules. Upon detecting an interference, the WIDS chooses whether to generate an alarm based on user alarm configurations. The WIDS can also take countermeasures for unauthorized devices.</p> <p>Huawei eSight Full Product Datasheet, CH 12 eSight WLAN Manager; p. 53 (2013-09-03) Huawei Technologies Co., Ltd.; <i>see also</i> eSight V300R007C00 Product Description, Issue 09 (2018-02-08) at p. 58-59 (indicating that, on information and belief, all versions of eSight incorporate WIDS).</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<div data-bbox="594 386 1549 630" style="border: 1px solid black; padding: 10px; margin: 10px auto; width: 80%;"> <p><b>Rich Security Event Analysis Reports Showing Network Security Status</b></p> <p>eSight LogCenter collects security event logs about network security devices and systems, such as Huawei network UTM system, firewalls, intrusion protection system, and Anti-DDoS system, analyzes them, and generates reports to help users learn the network security status. eSight LogCenter supports DDoS attack event analysis, plug-in block analysis, access control event analysis, policy matching analysis, IPS analysis, URL filter analysis, and email filter analysis.</p> </div> <p>Huawei eSight Full Product Datasheet, CH 11 eSight LogCenter Manager; p. 44 (2013-09-03) Huawei Technologies Co., Ltd.</p> <p>Security</p> <p>Users can monitor rogue devices, clients, interference sources, and attacks on the network, define rules to identify intrusion devices, generate remote alarm notifications, and take measures to prevent intrusions.</p> <ol style="list-style-type: none"> <li>1. Supports statistics and display of and countermeasure against rogue devices.</li> <li>2. Supports the display of and countermeasure against rogue clients and suppression access protection.</li> <li>3. Supports statistics and display of non-Wi-Fi interference sources.</li> <li>4. Supports statistics and display of attacks and protection against attacks.</li> <li>5. Allows users to define rules and classify rogue APs (rogue, suspected-rogue, adjacent, suspected-adjacent, and interference). Supported rule matching indicators include</li> </ol>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>adjacent- or same-frequency interference, signal strength, SSID (fuzzy match/regular expression), the number of detected APs, and whether to attack.</p> <p>eSight V300R007C00 Product Description, Issue 09 (2018-02-08) at p. 63.</p>
<p><b>[c]</b> monitoring transmissions among said plurality of stations to detect failed attempts to authenticate MAC addresses; and</p>	<p>The '678 Patent Accused Products comprise policing stations, as described above in [b], that are capable of monitoring transmissions among said plurality of stations to detect failed attempts to authenticate MAC addresses.</p> <p>For example, the policing station is capable of detecting when an intruder attempts to authenticate a MAC address using Brute Force Cracking in which there are failed attempts to authenticate.</p> <p>2.4 WIDS Attack Detection</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>To protect a WLAN against attacks, you can configure real-time attack detection on APs. When detecting abnormal behavior or packets, the system considers that it is attacked and performs automatic security protection.</p> <div data-bbox="766 500 1480 966" data-label="Diagram"> <p style="text-align: center;"><b>Figure 2-9 WIDS attack: detection scenario</b></p> <p>The diagram illustrates a WIDS attack detection scenario. At the top, an AC (Access Controller) is connected to an IP network cloud. The IP network cloud is connected to three APs (Access Points). Below the APs, there are three STAs (Stations). The leftmost STA is labeled 'Malicious STA' and is sending an 'Attack' signal to the leftmost AP. The middle STA is labeled 'STA' and is connected to the middle AP. The rightmost STA is labeled 'Malicious STA' and is sending an 'Attack' signal to the rightmost AP. The APs are connected to the IP network cloud, which is connected to the AC.</p> </div> <p>On the WLAN shown in the preceding figure, WIDS attack detection can be enabled on the AC when the WLAN access service is provided. The WIDS can detect 802.11 flood attacks, spoofing attacks, and weak initialization vector (IV) attacks, and can also defend the WLAN against brute force cracking.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 12.</p> <p>2.4.4 Defense Against Brute Force Cracking</p> <p>A brute force attack, or exhaustive key search, is a cryptanalytic attack that tries every possible password combination to find the real password. For example, a password that contains only</p>


**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>four digits may have a maximum of 10,000 combinations. The password can be cracked after a maximum of 10,000 attempts. Theoretically, an attacker can use the brute force method to crack any password. The cracking duration varies depending on the security mechanism and password length. Therefore, brute force cracking threats exist when any authentication mode is used.</p> <ul style="list-style-type: none"> <li>● When a WLAN uses the WPA/WPA2-PSK, WAPI-PSK, or WEP-Shared-Key security policy (link authentication), attackers may use the brute force method to crack passwords.</li> <li>● When a user authentication mode is used, such as MAC address, Portal, or 802.1X authentication, brute force cracking threats also exist.</li> </ul> <p>Huawei Technologies Co., Ltd. WLAN WIDS &amp; WIPS Technology White Paper; Issue 2.0 (2017-07-05) at 15.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

**'678 PATENT  
CLAIM 12**

**INFRINGEMENT BY HUAWEI CORPORATION**



When different user access authentication modes are used, such as MAC address, Portal, and 802.1X authentication, defense against brute force cracking is also needed. The basic principle is similar, which is described as follows:

- MAC address authentication: The MAC address of a STA is used as an account and sent to the RADIUS server for authentication. If authentication fails, the STA is added

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**


'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>to the STA blacklist and prohibited from accessing the network within a short time period (configurable and 60s by default).</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 16.</p> <p>The Huawei eSight Platform further incorporates the WIDS system and monitors transmissions among the stations as indicated above.</p> <p>Wireless Network Security Detection</p> <p>The Wireless Intrusion Detection System (WIDS) monitors intrusion devices and non-Wi-Fi interferences and provides frequency spectrum analysis features.</p> <p>WIDS management: The WIDS manages wireless network interferences in different categories. Interferences are classified based on user customized rules. Upon detecting an interference, the WIDS chooses whether to generate an alarm based on user alarm configurations. The WIDS can also take countermeasures for unauthorized devices.</p> <p>Huawei eSight Full Product Datasheet, CH 12 eSight WLAN Manager; p. 53 (2013-09-03) Huawei Technologies Co., Ltd.; <i>see also</i> eSight V300R007C00 Product Description, Issue 09 (2018-02-08) at p. 58-59 (indicating that, on information and belief, all versions of eSight incorporate WIDS).</p> <p>WIDS Wireless Intrusion Detection System</p> <p>The Wireless Intrusion Detection System (WIDS) manages information about rogue devices, interference resources, and attacks, and supports type-based recognition and alarm notification based on user-defined rules. Besides, the WIDS allows users to take countermeasures against unauthorized devices, ensuring wireless network security.</p>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>...</p> <p>Network administrators can classify and filter rogue APs and management alarms based on defined rules. Rule definition involves the following indicators: SSID, channel, field strength, impact scope, and attack behavior. Users can enable eSight to generate alarms when rogue APs in compliance with defined rules are detected.</p> <p>Same or adjacent channel</p> <p>This rule is used to detect the channel deployment of APs, and detect rogue APs that operate in the same or adjacent channel. If rogue APs operate in the same channel with normal APs, eSight regards it as same-frequency interference; if rogue APs operate in an adjacent channel, eSight regards it as adjacent-frequency interference</p>




**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	 <p>The screenshot shows a configuration window for a rule. The 'Name' field is empty. The 'Classification' dropdown is set to 'Rogue'. The 'Enable' radio buttons are set to 'Yes'. The 'Send alarm' section has an information icon and the text 'Send an alarm when an AP applies to this rule.' with radio buttons set to 'No'. The 'Discovery filter' section is highlighted with a red box and contains a dropdown menu set to 'Same/Neighboring Channel' with an 'Add' button. Below this is a 'Channel' section with a green arrow icon. The 'Channel type' dropdown is open, showing 'Same Channel' (highlighted), 'Same Channel', and 'Neighboring Channel'. At the bottom are 'Confirm' and 'Cancel' buttons.</p> <p>HUAWEI eSight WLAN Technology White Paper, Issue 01 (2017-03-20) at 10-12.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
<p><b>[d]</b> generating an intrusion alert based upon detecting a number of failed attempts to authenticate a MAC address.</p>	<p>As described above, on information and belief, the policing stations are capable of generating an intrusion alert based upon detecting a number of failed attempts to authenticate a MAC address. For example, if the AP considers that the STA is using the brute force cracking, it generates and sends an alarm to the AC, and on information and belief, such alarm is generated in the event of a MAC address brute force cracking attempt:</p> <p style="padding-left: 40px;">An AP checks whether the number of key negotiation attempts within a specified time period during WPA/WPA2-PSK, WAPI-PSK, or WEP-Shared-Key authentication exceeds the specified threshold (configurable). If so, the AP considers that the STA is using the brute force method to crack the password and reports an alarm to the AC.</p> <p style="padding-left: 40px;">...</p> <p>When different user access authentication modes are used, such as MAC address, Portal, and 802.1X authentication, defense against brute force cracking is also needed. The basic principle is similar, which is described as follows:</p> <ul style="list-style-type: none"> <li>● MAC address authentication: The MAC address of a STA is used as an account and sent to the RADIUS server for authentication. If authentication fails, the STA is added to the STA blacklist and prohibited from accessing the network within a short time period (configurable and 60s by default).</li> </ul> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 15-16.</p> <p>Defense against PSK cracking: Security authentication modes for wireless users include WEP shared key, WPA/WPA2 PSK, WPA/WPA2 dot1x, WAPI certificate, and WAPI PSK. Theoretically, if a client keeps exhaustive key search, it can crack the key. Therefore, a protection mechanism is added so that when the number of authentication attempts exceeds a specified threshold, packets from the client are discarded in a specified time to prevent the user</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>from continuous brute force attacks, reducing the adverse effects of frequent negotiations on devices and the network.</p> <p>WLAN WIDS Technology White Paper, Issue 1.0 (2014-04-24) at 12.</p>  <pre> sequenceDiagram     participant STA     participant AP     participant AC      Note over STA,AP: Brute force PSK cracking     Note over STA,AP: Brute force WEP-Shared-Key cracking      AP-&gt;&gt;AC: Send a PSK authentication request to the AC for processing.     AC-&gt;&gt;AC: Detect a brute force PSK cracking attack.     AC-&gt;&gt;AC: Add the attacker to the dynamic blacklist.     AC-&gt;&gt;AP: Deliver the dynamic blacklist.     AC-&gt;&gt;AC: Record logs and alarms.     AP-&gt;&gt;AC: Report attack detection information.     AC-&gt;&gt;AC: Add the attacker to the dynamic blacklist.     AC-&gt;&gt;AP: Deliver the dynamic blacklist.     AC-&gt;&gt;AC: Record logs and alarms.   </pre> <p>The diagram illustrates a sequence of events between a Station (STA), an Access Point (AP), and an Access Controller (AC). STA sends brute force attacks (PSK and WEP-Shared-Key cracking) to AP. AP sends a PSK authentication request to AC. AC detects the PSK attack, adds the attacker to a dynamic blacklist, and delivers the blacklist to AP. AC also records logs and alarms. AP reports attack detection information to AC. AC adds the attacker to the dynamic blacklist again, delivers the blacklist to AP, and records logs and alarms.</p>


**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 16.</p> <p>As described in Huawei Support documentation, a number of failed attempts to authenticate the MAC address results in locking the user account, which, on information and belief, triggers the generation of an alarm as described above:</p> <p style="padding-left: 40px;">By default, the account locking function is enabled on the AC to ensure security of user passwords. If a user fails authentication over 30 times within 30 minutes, the AC locks the user account for a specified period of time, during which this account cannot be authenticated.</p> <p style="padding-left: 40px;">Some terminals initiate MAC address authentication but do not initiate Portal authentication several times after associating with SSIDs. (For example, background applications on a mobile phone initiate multiple TCP requests instantly after the mobile phone associates with an SSID.) If the MAC address of a terminal is not recorded in the AAA server, and the terminal fails authentication over 30 times within 30 minutes, the AC locks the user account (the terminal's MAC address). Therefore, the terminal fails MAC address authentication and the Portal authentication page is displayed.</p> <p>Huawei Community Forums, [From Beginner to Expert - WLAN Fundamentals] Section 11 - WLAN Access Authentic. Jun 25, 2016 (at <a href="https://forum.huawei.com/enterprise/en/From-Beginner-to-Expert-WLAN-Fundamentals-Section-11-WLAN-Access-Authentic/thread/346361-869">https://forum.huawei.com/enterprise/en/From-Beginner-to-Expert-WLAN-Fundamentals-Section-11-WLAN-Access-Authentic/thread/346361-869</a>)</p> <p>Further, eSight generates an intrusion alert based upon detecting a number of failed attempts to authenticate a MAC address, including by utilizing WIDS as described above; further, rogue devices may trigger alarms. For example:</p> <p style="padding-left: 40px;">Security</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Users can monitor rogue devices, clients, interference sources, and attacks on the network, define rules to identify intrusion devices, generate remote alarm notifications, and take measures to prevent intrusions.</p> <ol style="list-style-type: none"> <li>1. Supports statistics and display of and countermeasure against rogue devices.</li> <li>2. Supports the display of and countermeasure against rogue clients and suppression access protection.</li> <li>3. Supports statistics and display of non-Wi-Fi interference sources.</li> <li>4. Supports statistics and display of attacks and protection against attacks.</li> <li>5. Allows users to define rules and classify rogue APs (rogue, suspected-rogue, adjacent, suspected-adjacent, and interference). Supported rule matching indicators include adjacent- or same-frequency interference, signal strength, SSID (fuzzy match/regular expression), the number of detected APs, and whether to attack.</li> </ol> <p>eSight V300R007C00 Product Description, Issue 09 (2018-02-08) at p. 63; <i>see also id.</i> at 74 (3. eSight supports alarms about communications, environments, rogue devices, non-Wi-Fi interference sources, and attacks to help users locate and resolve faults.).</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 12	INFRINGEMENT BY HUAWEI CORPORATION
	<p style="text-align: center;">24/7 Alarm Monitoring and Real-Time Notifications Are Displayed in Multiple Ways</p>  <p style="text-align: center;">eSight Overview Presentation at 11.</p>
'678 PATENT CLAIM 13	INFRINGEMENT BY HUAWEI CORPORATION
<p><b>13.</b> The wireless network of claim 12 wherein said policing station generates an intrusion alert based upon detecting the</p>	<p>The Huawei '678 Accused Products infringe this claim. <i>See</i> Claim 12. Such Instrumentalities further have a policing station capable of generating an intrusion alert based upon detecting the number of failed attempts to authenticate the MAC address within a predetermined period.</p>


**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 13	INFRINGEMENT BY HUAWEI CORPORATION
number of failed attempts to authenticate the MAC address within a predetermined period.	<p>For example, as described in the WIDS Technology White Paper, on information and belief, an alarm is generated from the AP after a threshold number of authentication attempts:</p> <p style="padding-left: 40px;">An AP checks whether the number of key negotiation attempts within a specified time period during [] authentication exceeds the specified threshold (configurable). If so, the AP considers that the STA is using the brute force method to crack the password and reports an alarm to the AC.</p> <p style="padding-left: 40px;">...</p> <p style="padding-left: 40px;">When different user access authentication modes are used, such as MAC address, Portal, and 802.1X authentication, defense against brute force cracking is also needed. The basic principle is similar, which is described as follows:</p> <ul style="list-style-type: none"> <li>● MAC address authentication: The MAC address of a STA is used as an account and sent to the RADIUS server for authentication. If authentication fails, the STA is added to the STA blacklist and prohibited from accessing the network within a short time period (configurable and 60s by default).</li> </ul> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 15-16.</p> <p>Further, a detection period and detection threshold may be set that, on information and belief, would include the failed attempts to authenticate the MAC address:</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

**'678 PATENT  
CLAIM 13**

**INFRINGEMENT BY HUAWEI CORPORATION**



1. The dynamic blacklist function is configured on the AC and the blacklist entry aging time is specified.

2. The AC sends the dynamic blacklist enabled flag and blacklist entry aging time to the AP.



**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 13	INFRINGEMENT BY HUAWEI CORPORATION
	<p>3. The WIDS attack detection mode is configured on the AC. The detection period and detection threshold (number of packets detected within the specified time period to identify an attack) are set.</p> <p>4. The AC delivers the detection mode, detection period, and detection threshold to the AP.</p> <p>5. The AP detects attacks in attack detection mode delivered by the AC.</p> <p>6. When the AP detects an attack, it reports attack information to the AC, such as the MAC address of the attacking device and the attack type. After receiving the attack information, the AC adds the attacking device to the attacking device list. If the AP detects no attack from this attacking device in the next three attack detection periods, it requests the AC to delete the attacking device from the list.</p> <p>7. The AC determines whether to add the attacking device to the dynamic blacklist. It records detected brute force PSK crackers to the dynamic blacklist cache table, and delivers the table to the AP.</p> <p>8. The AC collects statistics on attack types and sends trap messages to report the attack types to the NMS.</p> <p>9. After receiving the dynamic blacklist, the AP discards the packets from the attacking devices in the dynamic blacklist.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 17.</p> <p>As described in Huawei Support documentation, for example, the AC may also detect the number of failed attempts to authenticate the MAC address (e.g., over 30 times) within a predetermined period (e.g.,</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 13	INFRINGEMENT BY HUAWEI CORPORATION
	<p>within 30 minutes) which, on information and belief, triggers the generation of an alarm or intrusion alert as described above:</p> <p style="padding-left: 40px;">By default, the account locking function is enabled on the AC to ensure security of user passwords. If a user fails authentication over 30 times within 30 minutes, the AC locks the user account for a specified period of time, during which this account cannot be authenticated.</p> <p style="padding-left: 40px;">Some terminals initiate MAC address authentication but do not initiate Portal authentication several times after associating with SSIDs. (For example, background applications on a mobile phone initiate multiple TCP requests instantly after the mobile phone associates with an SSID.) If the MAC address of a terminal is not recorded in the AAA server, and the terminal fails authentication over 30 times within 30 minutes, the AC locks the user account (the terminal's MAC address). Therefore, the terminal fails MAC address authentication and the Portal authentication page is displayed.</p> <p>Huawei Community Forums, [From Beginner to Expert - WLAN Fundamentals] Section 11 - WLAN Access Authentic. Jun 25, 2016 (at <a href="https://forum.huawei.com/enterprise/en/From-Beginner-to-Expert-WLAN-Fundamentals-Section-11-WLAN-Access-Authentic/thread/346361-869">https://forum.huawei.com/enterprise/en/From-Beginner-to-Expert-WLAN-Fundamentals-Section-11-WLAN-Access-Authentic/thread/346361-869</a>)</p> <p>eSight is also involved in the generation of intrusion alerts, for example:</p> <p style="padding-left: 40px;">Security</p> <p style="padding-left: 40px;">Users can monitor rogue devices, clients, interference sources, and attacks on the network, define rules to identify intrusion devices, generate remote alarm notifications, and take measures to prevent intrusions.</p> <p style="padding-left: 40px;">1. Supports statistics and display of and countermeasure against rogue devices.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 13	INFRINGEMENT BY HUAWEI CORPORATION
	<p>2. Supports the display of and countermeasure against rogue clients and suppression access protection.</p> <p>3. Supports statistics and display of non-Wi-Fi interference sources.</p> <p>4. Supports statistics and display of attacks and protection against attacks.</p> <p>5. Allows users to define rules and classify rogue APs (rogue, suspected-rogue, adjacent, suspected-adjacent, and interference). Supported rule matching indicators include adjacent- or same-frequency interference, signal strength, SSID (fuzzy match/regular expression), the number of detected APs, and whether to attack.</p> <p>eSight V300R007C00 Product Description, Issue 09 (2018-02-08) at p. 63; <i>see also id.</i> at 74 (3. eSight supports alarms about communications, environments, rogue devices, non-Wi-Fi interference sources, and attacks to help users locate and resolve faults.).</p>
'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
<p><b>17.</b> The wireless network of claim 12 wherein the wireless network has at least one service set identification (ID) associated therewith; and wherein said policing station further detects intrusions into the wireless network by:</p>	<p>The Huawei '678 Accused Products infringe this claim. <i>See</i> Claim 12. Further, the wireless network has at least one service set identification (ID) associated therewith.</p> <p>Most wireless networks have an SSID associated therewith. As a non-limiting example, as described in the WIDS and WIPS whitepaper, a company WLAN may have an associated SSID:</p> <p style="padding-left: 40px;">In this case, company B can add the SSID of company A's WLAN to the SSID whitelist so that APs in company A will not be detected as rogue devices...</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 22.</p> <p style="padding-left: 40px;">3.1.9 SSID Profile</p> <p style="padding-left: 40px;">SSIDs identify different wireless networks. When you search for available wireless networks on your laptop, the displayed wireless network names are SSIDs.</p> <p style="padding-left: 40px;">An SSID profile is used to configure the SSID name and other access parameters of a WLAN.</p> <p>HUAWEI WLAN Typical Configuration Examples, Issue 01 (2017-12-29) at 24.</p>


**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<div data-bbox="821 446 1461 1175"><p>The diagram illustrates a network topology for Company A. At the top, an Access Controller (AC) is connected to a cloud labeled 'Company A'. The cloud is associated with the SSID 'Corp', which is circled in red. Three Access Points (APs) are connected to the cloud. Below the cloud, there are two Rogue Access Points: 'Rogue AP 1' with SSID 'Jack' and 'Rogue AP 2' with SSID 'Corp'. 'Rogue AP 2' is also circled in red. A red arrow points from 'Rogue AP 2' to a laptop labeled 'STA C'. There are also several other laptops shown in the network.</p></div> <p>...Rogue AP 2 uses the same SSID as the WLAN system of the company...</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 22-23 (emphasis added).</p> <p>As further described in the eSight documentation, eSight using WIDS also detects intrusions in the wireless network in accordance with the claim as described below</p> <p style="padding-left: 40px;">WIDS Wireless Intrusion Detection System</p> <p style="padding-left: 40px;">The Wireless Intrusion Detection System (WIDS) manages information about rogue devices, interference resources, and attacks, and supports type-based recognition and alarm notification based on user-defined rules. Besides, the WIDS allows users to take countermeasures against unauthorized devices, ensuring wireless network security.</p> <p style="padding-left: 40px;">...</p> <p style="padding-left: 40px;">Network administrators can classify and filter rogue APs and management alarms based on defined rules. Rule definition involves the following indicators: SSID, channel, field strength, impact scope, and attack behavior. Users can enable eSight to generate alarms when rogue APs in compliance with defined rules are detected.</p> <p style="padding-left: 40px;">SSID</p> <p style="padding-left: 40px;">The service set identifiers of networks from unauthorized vendors or wireless networks established by individuals are similar to authorized SSIDs. For example, the SSIDs are the same or characters are similar (such as 0 and o). In this case, users may be deceived to log in to rogue wireless networks. An SSID rule can be used to detect rogue APs whose SSIDs are similar to the authorized SSIDs or when a specified rule (regular expression) is met.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**


'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	 <p>HUAWEI eSight WLAN Technology White Paper, Issue 01 (2017-03-20) at 10-12.</p>
[a] monitoring transmissions among said plurality of stations to detect service set IDs associated therewith; and	The Huawei '678 Patent Accused Products comprise a policing station that can monitor transmissions among the plurality of stations to detect service set IDs associated therewith. For example, the monitor AP collects neighbor information including SSIDs:

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

**'678 PATENT  
CLAIM 17**

**INFRINGEMENT BY HUAWEI CORPORATION**

**Figure 4-3** Unauthorized AP deployment in a company



As shown in the preceding figure, employees deploy unauthorized APs (rogue APs 1 and 2, which are Fat APs or smart terminals with the AP function enabled) to the WLAN of a company. Rogue AP 1 uses the SSID **Jack** and provides wireless services for an employee's own STA (such as a tablet). The company's WLAN may be interfered, causing leakage of the company's information assets. Rogue AP 2 uses the same SSID as the WLAN system of the company, and attempts to steal company information assets by forging an authorized AP and establishing connections with devices in the company.



**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<p>In this case, the WIDS and WIPS functions can be enabled on the company's WLAN to contain rogue APs using the same SSID. After the WIDS and WIPS functions are configured on the AC, the monitor AP collects information about neighboring device and reports the information to the AC. When the AC identifies a rogue AP, it notifies the monitor AP of the rogue AP's identity information. The monitor AP then uses the rogue AP's identity information to broadcast a Deauthentication frame. After STAs associating with the rogue AP receive the Deauthentication frame, they disassociate from the rogue AP. This containment mechanism prevents STAs from associating with the rogue AP.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 22-23 (emphasis added).</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION																						
	<div data-bbox="674 386 1635 1011" style="border: 1px solid black; padding: 10px; margin: 10px auto; width: 80%;"> <p><b>Table 2-3</b> Key information about a detected wireless device</p> <table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>MAC address</td><td>MAC address of the device</td></tr> <tr> <td>BSSID</td><td>BSSID of the device</td></tr> <tr> <td>Type</td><td>Ad hoc device, AP, STA, or wireless bridge</td></tr> <tr> <td>SSID</td><td>SSID of an ESS</td></tr> <tr> <td>Vendor</td><td>Vendor of the device</td></tr> <tr> <td>Channel</td><td>Channel in which the device is detected for the last time</td></tr> <tr> <td>RSSI</td><td>Maximum RSSI of the device</td></tr> <tr> <td>Beacon Interval</td><td>Interval at which an AP or ad hoc device sends Beacon frames</td></tr> <tr> <td>First Detected Time</td><td>First time at which the device is detected</td></tr> <tr> <td>Last Detected Time</td><td>Last time when the device is detected</td></tr> </table> </div> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 9.</p> <p>Further, the WIDS system, including as used in eSight, monitors transmissions among said plurality of stations to detect service set IDs associated therewith:</p> <p style="text-align: center;">WIDS Wireless Intrusion Detection System</p>	Attribute	Description	MAC address	MAC address of the device	BSSID	BSSID of the device	Type	Ad hoc device, AP, STA, or wireless bridge	SSID	SSID of an ESS	Vendor	Vendor of the device	Channel	Channel in which the device is detected for the last time	RSSI	Maximum RSSI of the device	Beacon Interval	Interval at which an AP or ad hoc device sends Beacon frames	First Detected Time	First time at which the device is detected	Last Detected Time	Last time when the device is detected
Attribute	Description																						
MAC address	MAC address of the device																						
BSSID	BSSID of the device																						
Type	Ad hoc device, AP, STA, or wireless bridge																						
SSID	SSID of an ESS																						
Vendor	Vendor of the device																						
Channel	Channel in which the device is detected for the last time																						
RSSI	Maximum RSSI of the device																						
Beacon Interval	Interval at which an AP or ad hoc device sends Beacon frames																						
First Detected Time	First time at which the device is detected																						
Last Detected Time	Last time when the device is detected																						

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<p>The Wireless Intrusion Detection System (WIDS) manages information about rogue devices, interference resources, and attacks, and supports type-based recognition and alarm notification based on user-defined rules. Besides, the WIDS allows users to take countermeasures against unauthorized devices, ensuring wireless network security.</p> <p>...</p> <p>Network administrators can classify and filter rogue APs and management alarms based on defined rules. Rule definition involves the following indicators: SSID, channel, field strength, impact scope, and attack behavior. Users can enable eSight to generate alarms when rogue APs in compliance with defined rules are detected.</p> <p>Same or adjacent channel</p> <p>This rule is used to detect the channel deployment of APs, and detect rogue APs that operate in the same or adjacent channel. If rogue APs operate in the same channel with normal APs, eSight regards it as same-frequency interference; if rogue APs operate in an adjacent channel, eSight regards it as adjacent-frequency interference</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<div data-bbox="585 386 1570 1214"> <p>* Name: <input type="text"/></p> <p>* Classification: <input type="text" value="Rogue"/></p> <p>* Enable: <input checked="" type="radio"/> Yes <input type="radio"/> No</p> <p>* Send alarm:   <input checked="" type="radio"/> Send an alarm when an AP applies to this rule.  <input type="radio"/> Yes <input checked="" type="radio"/> No</p> <div> <p><b>Discovery filter</b></p> <p>Same/Neighboring Channel <input type="button" value="+ Add"/></p> <p>↓ Channel</p> <p>Channel type: <input type="text" value="Same Channel"/></p> <p>Same Channel Neighboring Channel</p> </div> <p><input type="button" value="Confirm"/> <input type="button" value="Cancel"/></p> </div> <p>SSID</p>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<div data-bbox="667 386 1520 971" data-label="Form"> <p>The screenshot shows a configuration window for a network rule. The 'Name' field is empty. The 'Classification' dropdown is set to 'Rogue'. The 'Enable' radio buttons are set to 'Yes'. The 'Send alarm' section has an information icon and the text 'Send an alarm when an AP applies to this rule.' with 'Yes' and 'No' radio buttons. The 'Discovery filter' section is highlighted with a red box and contains a table with one row: 'SSID' with a green arrow icon. Below the table, the 'SSID' field is set to 'Fuzzy matching'. At the bottom are 'Confirm' and 'Cancel' buttons.</p> </div> <p data-bbox="638 1084 1755 1300">The service set identifiers of networks from unauthorized vendors or wireless networks established by individuals are similar to authorized SSIDs. For example, the SSIDs are the same or characters are similar (such as 0 and o). In this case, users may be deceived to log in to rogue wireless networks. An SSID rule can be used to detect rogue APs whose SSIDs are similar to the authorized SSIDs or when a specified rule (regular expression) is met.</p> <p data-bbox="525 1333 1593 1365">HUAWEI eSight WLAN Technology White Paper, Issue 01 (2017-03-20) at 10-12.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
<p>[b] generating an intrusion alert based upon one of the detected service set IDs being different than the at least one service set ID of the wireless network.</p>	<p>The Huawei '678 Patent Accused Products generate an intrusion alert based upon one of the detected service set IDs being different than the at least one service set ID of the wireless network. For example, when an AP's SSID is different than the SSID of the WLAN, it may be considered a Rogue AP and a Rogue AP alarm is generated.</p> <p>When receiving information about neighboring devices reported by an AP, an AC starts rogue device identification. The following figure shows the rogue device identification process.</p> <p><b>Figure 2-7</b> Rogue device identification process</p> <pre> graph TD     A[Information about a wireless device reported by an AP] --&gt; B[Device type identification]     B --&gt; C[AP/Wireless bridge]     B --&gt; D[STA]     B --&gt; E[Ad hoc device]     C --&gt; F{Is the AP connected to the AC?}     F -- N --&gt; G{Is the SSID in the whitelist?}     G -- N --&gt; H[Rogue AP/wireless bridge]     D --&gt; I{Is the STA connected to the AC?}     I -- N --&gt; J{Is the peer end a rogue AP?}     J -- Y --&gt; K[Rogue STA]     E --&gt; L[Ad hoc device]   </pre>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 9.</p> <p>To ensure data security or prevent interference to a WLAN, a company generally forbids deployment of unauthorized APs. In this case, the company can enable the WIDS function to detect other WLAN devices that do not belong to its own WLAN.</p> <div data-bbox="667 602 1236 1218"> <p><b>Figure 4-3</b> Unauthorized AP deployment in a company</p> </div> <p>As shown in the preceding figure, employees deploy unauthorized APs (rogue APs 1 and 2, which are Fat APs or smart terminals with the AP function enabled) to the WLAN of a</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<p>company. Rogue AP 1 uses the SSID Jack and provides wireless services for an employee's own STA (such as a tablet). The company's WLAN may be interfered, causing leakage of the company's information assets. Rogue AP 2 uses the same SSID as the WLAN system of the company, and attempts to steal company information assets by forging an authorized AP and establishing connections with devices in the company.</p> <p>In this case, the WIDS and WIPS functions can be enabled on the company's WLAN to contain rogue APs using the same SSID. After the WIDS and WIPS functions are configured on the AC, the monitor AP collects information about neighboring device and reports the information to the AC. When the AC identifies a rogue AP, it notifies the monitor AP of the rogue AP's identity information. The monitor AP then uses the rogue AP's identity information to broadcast a Deauthentication frame. After STAs associating with the rogue AP receive the Deauthentication frame, they disassociate from the rogue AP. This containment mechanism prevents STAs from associating with the rogue AP.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 22-23.</p> <p>Rogue APs: Currently, Huawei WLAN devices support containment against ...rogue APs with bogus SSIDs.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 11.</p> <p>If the device type is AP or wireless bridge, the AC first checks whether it is an authorized device. If the BSSID of the device is the same as that of another device currently managed by the AC, it is an authorized device. Otherwise, the identification continues. If the SSID of the device (such as CMCC) is in the SSID whitelist configured</p>



**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<p>by the administrator, it is an authorized device. Otherwise, the device is identified as a rogue device.</p> <p>....</p> <p>When the AC identifies an AP as a rogue AP, a rogue AP alarm is triggered and sent to the network management system (NMS) in an SNMP trap.</p> <p>Huawei Technologies Co., Ltd. WLAN WIDS &amp; WIPS Technology White Paper; Issue 2.0 (2017-07-05) at 10.</p> <p>Further, the eSight White Paper describes using WIDS and generating an alarm based upon one of the detected service set IDs being different than the at least one service set ID of the wireless network:</p> <p>SSID</p> <p>The service set identifiers of networks from unauthorized vendors or wireless networks established by individuals are similar to authorized SSIDs. For example, the SSIDs are the same or characters are similar (such as 0 and o). In this case, users may be deceived to log in to rogue wireless networks. An SSID rule can be used to detect rogue APs whose SSIDs are similar to the authorized SSIDs or when a specified rule (regular expression) is met.</p>




**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<div data-bbox="667 386 1627 1047"> </div> <p>HUAWEI eSight WLAN Technology White Paper, Issue 01 (2017-03-20) at 10-12.</p> <p><i>See also:</i></p> <p>3.1.25 WIDS Spoof SSID Profile</p> <p>WLAN services are available in public places, such as banks and airports. Users can connect to the WLANs after associating with corresponding SSIDs. If a rogue AP is</p>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 17	INFRINGEMENT BY HUAWEI CORPORATION
	<p>deployed and provides spoofing SSIDs similar to authorized SSIDs, the users may be misled and connect to the rogue AP, which brings security risks. To address this problem, configure a fuzzy matching rule to identify spoofing SSIDs. The device compares a detected SSID with the matching rule. If the SSID matches the rule, the SSID is considered a spoofing SSID. The AP using the spoofing SSID is a rogue AP. After rogue AP containment is configured, the device contains the rogue AP and disconnects users from the spoofing SSID.</p> <p>For the detailed configuration, see (Optional) Configuring Fuzzy Matching Rules for Identifying Spoofing SSIDs in the Configuration-WLAN Security Configuration Guide.</p> <p>HUAWEI WLAN Typical Configuration Examples, Issue 01 (2017-12-29) at 33.</p>
'678 PATENT CLAIM 18	INFRINGEMENT BY HUAWEI CORPORATION
<p>18. The wireless network of claim 12 wherein said plurality of stations transmit data over at least one channel; and wherein said policing station further detects transmissions over the at least one channel not originating from one of the plurality of stations and generates an intrusion alert based thereon.</p>	<p>The Huawei '678 Patent Accused Products infringe this claim. <i>See</i> Claim 12. Further, said plurality of stations transmit data over at least one channel; and wherein said policing station further detects transmissions over the at least one channel not originating from one of the plurality of stations (e.g., neighboring devices) and generates an intrusion alert based thereon.</p> <p>For example:</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 18	INFRINGEMENT BY HUAWEI CORPORATION
	<p><b>Figure 2-2 Principles of the two working modes</b></p> <p><b>Normal mode</b></p> <p>The WISD and WIPS functions and other air interface scan functions are disabled.</p>  <p>The WISD and WIPS functions are enabled.</p>  <p><b>Monitor mode</b></p>  <p>Rogue devices are detected in all the channels of the frequency band on which the current radio works, or channels allowed by a specified country code.</p> <p><b>2.2.2 Wireless Device Identification</b></p> <p>On WLANs, APs, STAs, ad hoc devices, and wireless bridges need to be monitored. When an AP working in normal mode with air interface scan functions enabled on radios or in monitor mode, it can identify the types of neighboring wireless devices based on detected 802.11 management and data frames. The wireless device identification process is as follows:</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 18	INFRINGEMENT BY HUAWEI CORPORATION
	<ol style="list-style-type: none"> <li>1. On the AC, the AP is configured to work in monitor mode or in normal mode with air interface scan functions enabled on radios.</li> <li>2. The AC delivers the configuration to the AP.</li> <li>3. The AP scans channels to collect information about neighboring wireless devices, and listens on frames sent by neighboring wireless devices to identify device types. The AP listens on the following types of frames: <ul style="list-style-type: none"> <li>– Beacon</li> <li>– Association Request</li> <li>– Association Response</li> <li>– Reassociation Request</li> <li>– Reassociation Response</li> <li>– Probe Response</li> <li>– Data frame</li> </ul> </li> <li>4. The AP reports the identified device types to the AC. The AC then determines whether the identified devices are authorized and notifies the AP of rogue devices.</li> </ol> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 4.</p> <p>Further, monitor APs monitor neighboring channels and detect transmissions of neighboring wireless devices. If these devices are determined to be Rogue APs, an intrusion alert is generated.</p> <ul style="list-style-type: none"> <li>● Rogue AP: an unauthorized or malicious AP, which can be an AP that is connected to a network without permission, an unconfigured AP, a neighbor AP, or an AP manipulated by an attacker</li> </ul>


**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 18	INFRINGEMENT BY HUAWEI CORPORATION
	<p style="text-align: center;">...</p> <ul style="list-style-type: none"> <li>● Monitor AP: an AP that scans or listens on wireless channels and attempts to detect attacks to the wireless network.</li> </ul> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 2; <i>see also</i> WLAN WIDS Technology White Paper, Issue 1.0 (2014-04-24) at 3.</p> <p style="padding-left: 40px;">2.2 Rogue Device Detection</p> <p style="padding-left: 40px;">Rogue device detection of WLANs is enabled to monitor the entire network. Monitor APs are deployed on a WLAN that needs protection to monitor the entire network. The monitor APs can periodically listen on wireless signals to detect rogue devices.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 3.</p> <p style="padding-left: 40px;">After the WIDS and WIPS functions are configured on the AC, the monitor AP collects information about neighboring device and reports the information to the AC. When the AC identifies a rogue AP, it notifies the monitor AP of the rogue AP's identity information.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 23.</p> <p style="padding-left: 40px;">When the AC identifies an AP as a rogue AP, a rogue AP alarm is triggered and sent to the network management system (NMS) in an SNMP trap.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 10.</p>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 18	INFRINGEMENT BY HUAWEI CORPORATION
	<p>As further described in the eSight documentation:</p> <p>3.2.3 WIDS Wireless Intrusion Detection System</p> <p>The Wireless Intrusion Detection System (WIDS) manages information about rogue devices, interference resources, and attacks, and supports type-based recognition and alarm notification based on user-defined rules. Besides, the WIDS allows users to take countermeasures against unauthorized devices, ensuring wireless network security.</p> <p style="text-align: center;">...</p> <p>Network administrators can classify and filter rogue APs and management alarms based on defined rules. Rule definition involves the following indicators: SSID, channel, field strength, impact scope, and attack behavior. Users can enable eSight to generate alarms when rogue APs in compliance with defined rules are detected.</p> <ul style="list-style-type: none"> <li>● Same or adjacent channel</li> </ul>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 18	INFRINGEMENT BY HUAWEI CORPORATION
	<p>This rule is used to detect the channel deployment of APs, and detect rogue APs that operate in the same or adjacent channel. If rogue APs operate in the same channel with normal APs, eSight regards it as same-frequency interference; if rogue APs operate in an adjacent channel, eSight regards it as adjacent-frequency interference</p> <div data-bbox="804 542 1539 1159">  </div> <p>HUAWEI eSight WLAN Technology White Paper, Issue 1.0 (2017-03-20) at 10-12.</p>




***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 19	INFRINGEMENT BY HUAWEI CORPORATION
<p>19. The wireless network of claim 12 wherein said policing station further transmits an intrusion alert to at least one of said plurality of stations.</p>	<p>The Huawei '678 Patent Accused Products infringe this claim. <i>See</i> Claim 12. Further, said policing station further transmits an intrusion alert to at least one of said plurality of stations.</p> <p>For example, the monitor AP generates and transmits intrusion alert information to the AC, and the AC reports intrusion alert information to other APs:</p> <p style="padding-left: 40px;">On WLANs, APs, STAs, ad hoc devices, and wireless bridges need to be monitored. When an AP working in normal mode with air interface scan functions enabled on radios or in monitor mode, it can identify the types of neighboring wireless devices based on detected 802.11 management and data frames. The wireless device identification process is as follows:</p> <ol style="list-style-type: none"> <li>1. On the AC, the AP is configured to work in monitor mode or in normal mode with air interface scan functions enabled on radios.</li> <li>2. The AC delivers the configuration to the AP.</li> <li>3. The AP scans channels to collect information about neighboring wireless devices, and listens on frames sent by neighboring wireless devices to identify device types. The AP listens on the following types of frames: <ul style="list-style-type: none"> <li>– Beacon</li> <li>– Association Request</li> <li>– Association Response</li> <li>– Reassociation Request</li> </ul> </li> </ol>

***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 19	INFRINGEMENT BY HUAWEI CORPORATION
	<ul style="list-style-type: none"> <li>– Reassociation Response</li> <li>– Probe Response</li> <li>– Data frame</li> </ul> <p>4. The AP reports the identified device types to the AC. The AC then determines whether the identified devices are authorized and notifies the AP of rogue devices.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 4.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**



**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 19	INFRINGEMENT BY HUAWEI CORPORATION
	<p>detects no attack from this attacking device in the next three attack detection periods, it requests the AC to delete the attacking device from the list.</p> <p>7. The AC determines whether to add the attacking device to the dynamic blacklist. It records detected brute force PSK crackers to the dynamic blacklist cache table, and delivers the table to the AP.</p> <p>8. The AC collects statistics on attack types and sends trap messages to report the attack types to the NMS.</p> <p>9. After receiving the dynamic blacklist, the AP discards the packets from the attacking devices in the dynamic blacklist.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 17 (emphasis added).</p> <p>If so, the AP considers that the STA is using the brute force method to crack the password and reports an alarm to the AC.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 15.</p> <p><input type="checkbox"/> The AP listens on frames to collect information about neighboring wireless devices, and reports the information to the AC at the specified short interval. The AC then determines whether the wireless devices are rogue devices and delivers the identification result to the AP. When the wireless devices are scanned again by the AP, the AP automatically checks whether they are rogue devices based on the identification result sent by the AC.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 19	INFRINGEMENT BY HUAWEI CORPORATION
	<p>□ The AP reports full information about all detected wireless devices to the AC at the long interval for information synchronization. The AC then determines whether the wireless devices are rogue devices and delivers the identification result to the AP. When the wireless devices are scanned again by the AP, the AP automatically checks whether they are rogue devices based on the identification result sent by the AC.</p> <p>Huawei Technologies Co., Ltd. <i>WLAN WIDS &amp; WIPS Technology White Paper</i>; Issue 2.0 (2017-07-05) at 8.</p>
'678 PATENT CLAIM 20	INFRINGEMENT BY HUAWEI CORPORATION
<p>20. The wireless network of claim 12 wherein said policing station comprises a base station.</p>	<p>The Huawei '678 Patent Accused Products infringe this claim. <i>See</i> Claim 12.</p> <p>Further the policing station comprises a base station. For example, the monitor APs described above acts as a base station.</p> <p><i>See</i> Claim 12</p>
'678 PATENT CLAIM 51	INFRINGEMENT BY HUAWEI CORPORATION
<p><b>51.</b> An intrusion detection method for a wireless local or metropolitan area network comprising a plurality of</p>	<p>The Huawei '678 Patent Accused Products infringe this claim. Huawei makes, uses, sells, offers to sell and/or imports equipment used in wireless or metropolitan local area networks (WLAN products), and on information and belief, makes, uses, sells, offers to sell and/or imports such networks in the United States.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 51	INFRINGEMENT BY HUAWEI CORPORATION
stations, the method comprising:	<p>Such equipment and networks perform an intrusion detection method for a wireless local or metropolitan area network comprising a plurality of stations.</p> <p><i>See evidence for Claim 12[preamble].</i></p> <p>The method further comprises the steps below.</p>
<b>[a]</b> transmitting data between the plurality of stations using a media access layer (MAC), each of the stations having a respective MAC address associated therewith;	<p>Huawei '678 Patent Accused Products transmit data between the plurality of stations using a media access layer (MAC), each of the stations having a respective MAC address associated therewith.</p> <p><i>See evidence for Claim 12[a].</i></p>
<b>[b]</b> monitoring transmissions among the plurality of stations to detect failed attempts to authenticate MAC addresses; and	<p>Huawei '678 Patent Accused Products monitor transmissions among the plurality of stations to detect failed attempts to authenticate MAC addresses.</p> <p><i>See evidence for Claim 12[c].</i></p>
<b>[c]</b> generating an intrusion alert based upon detecting a number of failed attempts to authenticate a MAC address.	<p>Huawei '678 Patent Accused Products generate an intrusion alert based upon detecting a number of failed attempts to authenticate a MAC address.</p> <p><i>See evidence for Claim 12[d].</i></p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 52	INFRINGEMENT BY HUAWEI CORPORATION
<p><b>52.</b> The method of claim 51 wherein generating an intrusion alert based upon detecting a number of failed attempts to authenticate a MAC address comprises generating an intrusion alert based upon detecting the number of failed attempts to authenticate the MAC address within a predetermined period.</p>	<p>Huawei '678 Patent Accused Products infringe this claim. <i>See</i> Claim 51. Further, generating an intrusion alert based upon detecting a number of failed attempts to authenticate a MAC address comprises generating an intrusion alert based upon detecting the number of failed attempts to authenticate the MAC address within a predetermined period</p> <p><i>See</i> evidence for Claim 13.</p>
'678 PATENT CLAIM 56	INFRINGEMENT BY HUAWEI CORPORATION
<p><b>56.</b> The method of claim 51 wherein the wireless network has at least one service set identification (ID) associated therewith; and further comprising:</p>	<p>The Huawei '678 Patent Accused Products infringe this claim. <i>See</i> claim 51. Further, the wireless network has at least one service set identification (ID) associated therewith.</p> <p><i>See</i> evidence for Claim 17[preamble].</p>
<p><b>[a]</b> monitoring transmissions among the plurality of stations</p>	<p>The Huawei '678 Patent Accused Products monitor transmissions among the plurality of stations to detect service set IDs associated therewith.</p>

**Harris Corporation v. Huawei, et al - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 56	INFRINGEMENT BY HUAWEI CORPORATION
to detect service set IDs associated therewith; and	<i>See</i> evidence for Claim 17[a].
<b>[b]</b> generating an intrusion alert based upon one of the detected service set IDs being different than the at least one service set ID of the wireless network.	The Huawei '678 Patent Accused Products generate an intrusion alert based upon one of the detected service set IDs being different than the at least one service set ID of the wireless network.  <i>See</i> evidence for Claim 17[b].
'678 PATENT CLAIM 57	INFRINGEMENT BY HUAWEI CORPORATION
<b>57.</b> The method of claim 51 wherein transmitting data comprises transmitting data over at least one channel; and further comprising detecting transmissions over the at least one channel not originating from one of the plurality of stations and generating an intrusion alert based thereon.	The Huawei '678 Patent Accused Products infringe this claim. <i>See</i> claim 51. Further, transmitting data comprises transmitting data over at least one channel; and further comprising detecting transmissions over the at least one channel not originating from one of the plurality of stations and generating an intrusion alert based thereon.  <i>See</i> evidence for Claim 18.



***Harris Corporation v. Huawei, et al* - Case No. 2:18-cv-439**  
**Plaintiff's Disclosure of Asserted Claims and Infringement Contentions (Pat. L.R. 3-1 & 3-2)**  
**CORRECTED Exhibit E – U.S. Patent No. 7,224,678 ('678) – Claims 12-13, 17-20, 51-52, 56-58**

'678 PATENT CLAIM 58	INFRINGEMENT BY HUAWEI CORPORATION
<p><b>58.</b> The method of claim 51 further comprising transmitting the intrusion alert to at least one of the plurality of stations.</p>	<p>The Huawei '678 Patent Accused Products infringe this claim. <i>See</i> Claim 51. The instrumentalities further transmit the intrusion alert to at least one of the plurality of stations.</p> <p><i>See</i> evidence for Claim 19.</p>